



Ceiling Opening: 3-3/4" (95mm)

Complete fixture consists of the Housing, Trim and Frame-in Kit. Select each separately.

Reflector Trim	Frame-in Kit	Lamp
343WHWHX White paint cone/ White paint flange	Remodeler 3401MREX	37W MR16 IR
343CCDSTX Clear diffused cone/ Brushed Steel Flange	IC / AirSeal® 302MRAICEX	50W MR16 / 37W MR16 IR
343CCDWHX Clear diffused cone/ White paint flange		37W MR16 IR

Features

- 1. Housing:** 25 ga steel. Black painted finish.
- 2. Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation.
- 3. Flange:** Die-cast aluminum 0.060" (1.5mm) thick.
- 4. Aperture Cone:** 18ga. Spun aluminum, comfort clear diffused or painted in white.
- 5. Mounting Clips (2):** 24 ga. spring steel, zinc plated. Provides easy snap-in / snap-out action.
- 6. Lamp guard:** 2" (51mm) dia. borosilicate glass.
- 7. Adjustable Lampholder Support:** 27 ga. steel, rotates 358° horizontally and 0° to 35° vertically. Black painted finish. Can be locked in vertical position.

Note: For complete Frame-in Kit specifications, refer to the 300X series Frame-in Kit specification sheets.

Accessories

- AF2SY** Symmetric: Prismatic Spread Lens (55°).
- AF2AS** Asymmetric: Beam Elongator (5° x 55°).
- AF2LF** Light Frost: Softens light beam.
- AF2PF** Perimeter Frost.
- AF2UV** UV Filters: Blocks UV radiation.
- AF2IR** Infrared Filter: Block infrareds.
- 300XTC** Not compatible with all Frame-in Kits. See 300XTC specification sheet.

Labels

CSA, UL Suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	