



Ceiling Opening: 3-3/4" (95mm)

Complete fixture consists of the Trim and Frame-in Kit. Select each separately.

Reflector Trim		Frame-In Kit	Lamp
371FGSTX	White Frosted glass/ brushed steel flange	Remodeler 3401MREX	50W MR16 / 37W MR16 IR
371FGWHX	White Frosted glass/ white flange	Remodeler 300ESX	50W ES/ESD16 (GZ10)
		Non-IC 302MREX	50W MR16 / 37W MR16 IR
		Non-IC 302ESX	50W ES/ESD16 (GZ10)
		IC 302ESICX	50W ES/ESD16 (GZ10)
		AirSeal® / IC 302MRAICEX	50W MR16 / 37W MR16 IR
		AirSeal® / IC 302ESAICX	50W ES/ESD16 (GZ10)

Features

1. **Housing:** 25 ga steel. Black painted finish.
2. **Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation. (patent # 2,184,149)
3. **Flange:** Die-cast aluminum 0.060" (1.5mm) thick.
4. **Glass:** Silica sand glass 0.173" (4.4mm) thick. Soft diffusion for a smooth beam pattern.
5. **Lampholder Support:** 23ga. Spring steel.
6. **Mounting Clips (2):** 24 ga. stainless steel. Provides easy snap-in / snap-out action.
7. **Lamp guard:** 2" (51mm) dia. borosilicate glass.

Note: For complete Frame-In Kit specifications, refer to the 300X series specification sheets.

Accessories

- 300SQBK** Square plate black
- 300SQWH** Square plate white
- 300XTC** Thick ceiling housing kit

Labels

CSA, UL Suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	