



**Ordering Information**

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
37B70EWH	Matte White	ProSpec® 120V/277V track systems only.	Use one of:	70W Ceramic
37B70EBK	Matte Black	Not compatible with recessed track and Monopoint.	8316 8318 83W4 8314 83W6 83W7U 8317 8317U 8313 8318 83W7	Metal Halide

**Features**

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track.
- Ground Clip:** Ensures proper grounding of module.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Connector:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

**Electrical**

**Universal Electronic Ballast**

**Input Voltage:** 120V/277V

**Power Factor:** >0.99

**Input Power:** 77W

**Max Input Current:** 0.65A @ 120V/0.28A @ 277V

**Total Harmonic Distortion:** <10%

**ANSI Code:** M (C) 85, M (C) 98, M (C) 139, M (C) 143

Do not use on dimming circuit

**Finish**

All painted finishes are baked enamel.

**Labels**

UL, cUL

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	