



Ceiling Opening: 4-3/4" (121mm)

Complete fixture consists of the Trim and Frame-in Kit. Select each separately.

Reflector Trim	Frame-in Kit	Lamp
464BAX Specular black specular cone and white flange	Remodeler 400MRX Remodeler 3401MREX	75W MR16 / 50W MR16 IR 50W MR16 / 37W MR16 IR
464CLX Specular clear specular cone and white flange	Non-IC 402MRX Non-IC 402MREX	75W MR16 / 50W MR16 IR 75W MR16 / 50W MR16 IR
464GDX Specular gold specular cone and white flange	IC 402MRIC9X	50W MR16 / 37W MR16 IR
464CCDX Specular clear diffuse cone and white flange		

Features

1. **Housing:** 25 ga. galvanized steel.
2. **Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation.
3. **Flange Housing:** Cold rolled steel 22ga.
4. **Cone:** 18ga hydroformed aluminum.
5. **Adjustable Lampholder Assembly Support:** Die-cast aluminum, rotates 358° horizontally and 0° to 30° vertically. Can be locked in vertical position.
6. **Lampholder Assembly:** Die-cast aluminum; Can accommodate up to two accessories. Can be removed for front relamping by turning counterclockwise without removing the flange housing.
7. **Step Baffle:** Die-cast aluminum with stepped conical surface for low brightness. Can be removed easily with no tools to install the snoot accessories.
8. **Mounting Clips (2):** 24 ga. spring steel, zinc plated. Provides easy snap-in / snap-out action.
9. **Lamp Guard:** 2" (51mm) dia. clear soda lime glass.

Note: For complete Frame-in Kit specifications, see the 400X series specification sheets.

Accessories

- 0084BK** Conical steel snoot painted black outside, inside
- 0084WH** Conical steel snoot painted white outside / black inside
- 0084AL** Conical steel snoot painted aluminum outside / black inside
- 0085FG** Conical glass snoot frosted white

Square Faceplates

- 400SQBK** Square Plate Black
- 400SQWH** Square Plate White

Accessories (continued)

- 2" (51mm) dia. Specialized Filters and Louvers
- AF2SY** Symmetric: Prismatic Spread Lens (55°)
- AF2AS** Asymmetric: Beam Elongator (5°x55°)
- AF2LF** Light Frost softens light beam
- 7550FD** Frosted Lens
- AF2PF** Perimeter Frost
- AF2UV** UV Filters blocks UV radiation
- AF2IR** Infra-red Reduction
- AL2HC** Hex Cell Louver; matte black. Use only with shielded MR16 flat lens lamps.

Labels

CSA, UL
Suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	