



Ceiling Opening: 4-3/4" (121mm)

Complete fixture consists of the Trim and Frame-in Kit. Select each separately.

Reflector Trim		Frame-in Kit		Lamp
471FGSTX	White Frosted glass/ brushed steel flange	Remodeler	400MRX	50W MR16 / 37W MR16 IR
471FGWHX	White Frosted glass/ white flange	Remodeler	3401MREX	50W MR16 / 37W MR16 IR
		Non-IC	402MRX	50W MR16 / 37W MR16 IR
		Non-IC	402MREX	50W MR16 / 37W MR16 IR
		IC	402MRIC9X	50W MR16 / 37W MR16 IR

Features

- Housing:** 25 ga. galvanized steel.
- Residence Mounting Clips:** Factory-installed; zinc plated spring steel; free-hand installation.
- Flange:** Die-cast aluminum 0.156" (3.8mm) thick; available in steel brushed or painted white.
- Glass:** Silica sand glass 0.173" (4.4mm) thick. Soft diffusion for a smooth beam pattern.
- Lampholder Support:** 23ga. Spring steel.
- Mounting Clips (2):** 24ga. Spring steel, zinc plated. Provides easy snap-in / snap-out action.

Note: For complete Frame-in Kit specifications, see the 400X series specification sheets.

Accessories

Square Faceplates

- 400SQBK** Square Plate Black
- 400SQWH** Square Plate White

Labels

CSA, UL
Suitable for damp locations.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	