



## Order Information

Catalog No.	Lamps	Width	Length	Diffuser Extension	O.A. Extension
6776	1 Lt. - 75W A-19	5"	9"	2 7/8"	4 3/4"

## Features

- 1. Diffuser:** Translucent white, injected-molded polycarbonate—Lexan® Ultraviolet stabilized for outdoor applications. Shatter-resistant material meets requirements for high abuse areas. Attaches to housing with positive twist lock action. No tools required (unless tamper-proof screw is used).
- 2. Housing/Reflector:** Regressed, corrosion-resistant, one piece die-cast aluminum housing; matte black exterior finish. Integral semi-gloss white reflector, contoured to give maximum light output and assure uniform illumination. All painted finishes are baked enamel.
- 3. Concealed Gasket:** Black EPDM gasket assures weather-tight and bug-tight operation.
- 4. Fiberglass Insulation**
- 5. Tamper-Proofing:** Tightening of Allen head stainless steel screw (standard in housing) protects luminaire against tampering and pilferage. Use of tamper-proof screw is optional.
- 6. Cross Bar:** For mounting to 3" or 4" octagonal outlet box or "gem" box. Suitable for wall installation only.

## Electrical

No. 18 SF-1 leads. Porcelain socket-medium base. Fixture requires minimum 90° C rated supply wire.

## Labels

UL (Suitable for Wet Locations), I.B.E.W.

Lexan® is a registered trademark of General Electric Company.

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

Lightolier a Genlyte Thomas Company [www.lightolier.com](http://www.lightolier.com)  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2002 Genlyte Thomas Group LLC (Lightolier Division) • A0902

LIGHTOLIER®