



Ceiling Cutout: 8" (203 mm) Dia.

Reflector Trim	Frame-In Kit
8056TBW Clear Iridescence Free, White Flange	S7126HU 7" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam)
8056TBP Clear Iridescence Free, Polished Flange	S7218HU 7" aperture, 2 lamp 18W Quad Tube CFL (120/277V) 2-pin and 4-pin
8056CTBW Comfort Clear, White Flange	S7226HU 7" aperture, 2 lamp 26W Quad Tube CFL (120/277V) 2-pin and 4-pin
8056CTBP Comfort Clear, Polished Flange	Dimming Options:
	S7126H <input type="checkbox"/> or S7218H <input type="checkbox"/> or S7226H
	CU3 Lightolier PowerSpec 3% Dimming (120/277V)
	J1LD3 Lutron 5% Dimming (120V)
	J2LD3 Lutron 5% Dimming (277V)
	JUM7 Mark 7 Dimming (120/277V)
	J1MX Mark 10 Dimming (120V)
	J2MX Mark 10 Dimming (277V)
	Other dimming product available, please consult factory

Features

- Reflector:** 16 ga. Specular Alzak® aluminum. Iridescence Free™ finish. Self-flanged trim.
- Socket Cup:** Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Turbo Louver:** Radial assembly; Specular Alzak® aluminium, removable and keyed for orientation. 50° visual cutoff, medium beam.

Electrical

Note: For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL listed for through branch circuit wiring with max of (8) No. 12 AWG, 90° C supply conductors.

Options and Accessories

Emergency Add suffix **EM***
 Chicago Plenum Add suffix **LC**
 Existing/Thk. Ceiling **FA EC7***
 Emergency Ltg. Kit **FA EM3E*** (4 pin)
FA EM2T* (2 pin)

Options and Accessories (continued)

Fuse (Slow Blow) Add Suffix **F**
 *See Spec. Sheets: FAEC, FAEM
 Mounting Bars & Accessories; see Specification Sheet MBA.
 Sloped Ceiling Adapters; see Specification Sheet SCA.

Labels

UL listed for damp locations, I.B.E.W.

Alzak® is a registered trademark of ALCOA.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2011 Philips Group • F0711

