



Reflector Trim	Frame-In Kit
<b>8091CBW</b> White Cone, White Flange <b>8091CBA</b> Aluminum Cone, White Flange	<b>S6132BU</b> 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam) <b>Dimming Options:</b> <b>S6132B</b> <input type="checkbox"/> <b>CU3</b> Lightolier PowerSpec 3% Dimming (120/277V) <b>J1LD3</b> Lutron 5% Dimming (120V) <b>J2LD3</b> Lutron 5% Dimming (277V) <b>JUM7</b> Mark 7 Dimming (120/277V) <b>J1MX</b> Mark 10 Dimming (120V) <b>J2MX</b> Mark 10 Dimming (277V) Other dimming product available, please consult factory
	Remodeler Frame-In Kits
	<b>6126BURM</b> 6" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam) <b>6132BURM</b> 6" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam)

### Features

- Reflector:** 16 ga. Die-formed aluminum, Anobrite® finish.
- Socket Cup:** Effectively dissipates heat and positions lamp holder. Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Mounting Frame:** Galvanized steel for dry or plaster ceilings. Accepts other 6" Triple Tube reflectors (see S6132BU Spec Sheet).
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Electronic 120V-277V. UL listed for through branch circuit wiring with max of (8) No. 12AWG, 90°C supply conductors. Outboard-mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Cross Blade Louver:** Die-formed, 16 ga. aluminum, matte white or painted aluminum finish. Accepts lens (consult factory). 50° cutoff to lamp, medium beam. Keyed for orientation.

### Electrical

**Note:** For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

### Options and Accessories

**Other Louver Finishes** Consult Factory

- |                       |                       |
|-----------------------|-----------------------|
| Emergency             | Add suffix <b>EM*</b> |
| Chicago Plenum        | Use 6132BULC          |
| Existing/Thk. Ceiling | <b>FA EC6*</b>        |
| Emergency Ltg. Kit    | <b>FA EM3E*</b>       |
| Fuse (Slow Blow)      | Add Suffix <b>F</b>   |
- \*See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA.

Sloped Ceiling Adapters; see Specification Sheet SCA.

IC Frame available; see **C6CFL32** specification sheet.

### Labels

UL listed for damp locations.

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 www.lightolier.com © 2009 Philips Group • B0209

