



Ceiling Cutout: 8" (203 mm) Dia.

Reflector Trim	Frame-In Kit
8097 CBW White Cone, White Flange 8097 CBA Aluminum Cone, White Flange	S7126BU 7" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam) S7132BU 7" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam) S7142BU 7" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam) Dimming Options: S7132B <input type="checkbox"/> or S7142B <input type="checkbox"/> CU3 Lightolier PowerSpec 3% Dimming (120/277V) J1LD3 Lutron 5% Dimming (120V) J2LD3 Lutron 5% Dimming (277V) JUM7 Mark 7 Dimming (120/277V) J1MX Mark 10 Dimming (120V) J2MX Mark 10 Dimming (277V) Other dimming product available, please consult factory
	Remodeler Frame-In Kits
	7126BURM 7" aperture, 1 lamp 26W Triple Tube CFL (120/277V) 4-Pin (Amalgam)) 7132BURM 7" aperture, 1 lamp 26/32W Triple Tube CFL (120/277V) 4-Pin (Amalgam) 7142BURM 7" aperture, 1 lamp 26/32/42W Triple Tube CFL (120/277V) 4-Pin (Amalgam)

Features

- Reflector:** 16 ga. Die-formed aluminum, Anobrite® finish.
- Socket Cup:** Snaps onto reflector neck to assure consistently correct optical alignment without tools.
- Retaining Springs:** Precision-tooled steel friction springs secure reflector to mounting frame for quick, tool-less installation.
- Mounting Brackets:** 16 ga. steel. Adjust from inside of fixture. Use 3/4" or 1 1/2" lathing channel, 1/2" EMT, or optional mounting bars.
- Ballast/J-Box:** Outboard mounted to reduce heat transfer and maintain lamp efficacy and life. Service from below without tools.
- Cross Blade Louver:** Die-formed, 16 ga. aluminum, matte white or painted aluminum finish. Accepts lens (consult factory). 50° cutoff to lamp, medium beam. Keyed for orientation.

Electrical

Note: For ballast electrical data and latest lamp/ballast compatibility refer to "Ballast" specification sheet for complete electrical data.

UL Listed for through branch circuit wiring with max of (8) No 12 AWG, 90 degree C supply conductors.

Options and Accessories

Other Louver Finishes

Consult Factory

- Emergency Add suffix **EM***
- Chicago Plenum Add suffix **LC**
- Existing/Thk. Ceiling **FA EC7***

Options and Accessories (continued)

- Emergency Ltg. Kit **FA EM3E***
- FA EM4E***
- Fuse (Slow Blow) Add Suffix **F**
- *See Spec. Sheets: FAEC, FAEM

Mounting Bars & Accessories; see Specification Sheet MBA.
 Sloped Ceiling Adapters; see Specification Sheet SCA.

Labels

UL listed for damp locations, I.B.E.W.

Alzak® is a registered trademark of ALCOA.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2011 Philips Group • C0711

