



Ordering Information

Catalog No.	Mounting	Finish	Lamps
8275WH 8275BK	All Lytespan Track Systems	Matte White Matte Black	2 X 13W Quad Tube (Compact Fluorescent) GX23-2 Base

Features

1. **Attachment Fitting:** Molded polycarbonate integral color, fitting rotates into track and locks on with push tabs.
2. **Brass Contact:** Extends for connection to 2nd circuit in Advent® Lytespan track.
3. **Magnetic Ballasts (2)**
4. **Reflector:** Specular Plus®* finish.
5. **Push Tab:** Locks and detaches unit.
6. **Pivot Tension Mount:** 350° horizontal rotation.
7. **Yoke:** Extruded aluminum.

Finish

All painted finishes baked enamel.

* Specular Plus® is a registered trademark of MSC Laminates and Composites Inc.

Advent® is a registered trademark of Lightolier.

Job Information	Type:
Job Name:	
Cat. No.:	
Lamp(s):	
Notes:	

Lamp Performance Data

Lamp Watts (nominal)	13
Lumens (initial)	860
Rated Average Life	10,000 hrs.
Minimum Starting Temperature	32° F

DISTANCE FROM CEILING	Single Unit Track 2 Feet From Wall					Multiple Units					
	0'	1'	2'	3'	4'	← 2' →			← 3' →		
						□	□	□	□	□	□
1'	38.	16.	2.	1.	0.	44.	33.	44.	40.	14.	40.
2'	28.	16.	5.	1.	0.	38.	34.	38.	31.	19.	31.
3'	14.	9.	4.	1.	0.	22.	21.	22.	17.	13.	17.
4'	7.	5.	3.	1.	1.	14.	14.	14.	10.	9.	10.
5'	4.	3.	2.	1.	1.	9.	9.	9.	6.	6.	6.
6'	2.	2.	1.	1.	1.	6.	6.	6.	5.	5.	5.
7'	1.	1.	1.	1.	0.	4.	4.	4.	3.	3.	3.
8'	1.	1.	1.	1.	0.	3.	3.	3.	2.	2.	2.
9'	1.	1.	0.	0.	0.	2.	2.	2.	2.	2.	2.

DISTANCE FROM CEILING	Single Unit Track 3 Feet From Wall					Multiple Units					
	0'	1'	2'	3'	4'	← 3' →			← 4' →		
						□	□	□	□	□	□
1'	15.	10.	4.	1.	0.	18.	14.	18.	17.	8.	17.
2'	17.	12.	6.	2.	1.	22.	18.	22.	19.	11.	19.
3'	10.	8.	4.	2.	1.	15.	14.	15.	13.	9.	13.
4'	7.	5.	3.	2.	1.	11.	10.	11.	9.	7.	9.
5'	4.	4.	2.	2.	1.	8.	7.	8.	6.	5.	6.
6'	3.	2.	2.	1.	1.	6.	6.	6.	4.	4.	4.
7'	2.	2.	1.	1.	1.	4.	4.	4.	3.	3.	3.
8'	1.	1.	1.	1.	1.	3.	3.	3.	3.	3.	3.
9'	1.	1.	1.	1.	0.	3.	3.	3.	2.	2.	2.

Job Information Type: