



**Ordering Information**

Catalog No.	Finishes	Track Mountings	Lamps
8294EWH 8294EBK	Matte White Matte Black	All Lytespan Track Systems and Multipoint. DO NOT USE with any other mounting accessories, horizontally mounted wall track, or stem mounted radius track.	PAR20L 39W Metal Halide

**Features**

- Lamp Housing:** Die-cast aluminum with cool grip insulation band; a high temperature silicone rubber which allows aiming adjustments while fixture is on.
- Socket:** 5KV pulse rated ceramic body socket with nickel plated lamp contacts; leads encased in silicone coated fiberglass sleeving.
- Ballast:** High Power Factor electronic HID ballast with dry film capacitor and lamp ignitor. Housed in aluminum extrusion.
- Track Attachment Fitting:** Molded polycarbonate, rotates into track; integral polarity keyguard.
- Locking Lever:** Safety locking lever locks and supports fixture in track.
- Brass Contact:** Extends for connection to second circuit in Advent® Lytespan track.
- Pivots:** 180° horizontal and vertical rotation with tensioned mounts for controlled aim.
- Cowl:** Spring steel, holds lens and louver accessories in place.

**Options & Accessories**

Beam Elongator	AF25AS
Beam Smoother	AF25LF
Louver (Hex Cell)	AL25HC

**Finishes**

All painted finishes powder coated baked enamel.

**Electrical**

Input Watts: 44W  
Line Current: .37 Amps

**Labels**

UL, I.B.E.W.

Job Information	Type:
<b>Job Name:</b>	
<b>Cat. No.:</b>	
<b>Lamp(s):</b>	
<b>Notes:</b>	

Lightolier a Genlyte company [www.lightolier.com](http://www.lightolier.com)  
 631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710  
 We reserve the right to change details of design, materials and finish.  
 © 2006 Genlyte Group LLC • D0706

