



#### Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
83B39EWH 83B39EBK 83B39EAL	Matte White Matte Black Metallic Aluminum	All Lytespan® Track Systems and Multi-point. DO NOT USE with any other mounting accessories, stem mounted Radius® Track, ProSpec® Track systems, or ATOM. Can be wall mounted. NO REMOTE MOUNTING.	Use one of: <b>8313</b> <b>8314</b> <b>8316</b> <b>83W4</b> <b>83W6</b>	39W Ceramic Metal Halide

#### Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track, integral polarity key guard.
- Brass Contact:** Extends for connection to second circuit in Advent Lytespan track.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Connector:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc® Modular spots and wall wash fixtures.

#### Electrical

Electronic Ballast

<b>Input Voltage:</b>	120V, 60Hz
<b>Power Factor:</b>	High
<b>Input Power:</b>	44W
<b>Max. Input Current:</b>	0.37A
<b>Total Harmonic Distortion:</b>	<10%
<b>ANSI Code:</b>	M130

Do not use on dimming circuit.

#### Finish

All painted finishes are baked enamel.

#### Labels

UL, cUL

#### Job Information

#### Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710

We reserve the right to change details of design, materials and finish.

www.lightolier.com © 2008 Philips Group • B1108