



Ordering Information

| Catalog No. | Finishes | Track Mountings | Luminaires | Lamp |
|-------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|--------------------------|
| 83B39LEWH | Matte White | All Lytespan® Track Systems and Multi-point. DO NOT USE with any other mounting accessories, stem mounted Radius® Track, or ProSpec® Track systems, or ATOM. Can be wall mounted. | Use one of: | 39W Ceramic Metal Halide |
| 83B39LEBK | Matte Black | | 8313 83W4 | |
| 83B39LEAL | Metallic Aluminum | | 8314 83W6 8316 | |

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Track Attachment Fitting:** Molded polycarbonate; rotates into track, integral polarity key guard.
- Brass Contact:** Extends for connection to second circuit in Advent Lytespan track.
- Safety Locking Lever:** Locks and supports module in track.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

Electrical

Electronic Ballast

| | |
|-----------------------------------|---------------|
| Input Voltage: | 120V, 45-65Hz |
| Power Factor: | >0.99 |
| Input Power: | 43W |
| Max. Input Current: | 0.36A |
| Total Harmonic Distortion: | <5% |
| ANSI Code: | M130 |

Do not use on dimming circuit.

Finish

All painted finishes are baked enamel.

Labels

UL, cUL

| Job Information | Type: |
|------------------|-------|
| Job Name: | |
| Cat. No.: | |
| Lamp(s): | |
| Notes: | |

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • D1108