



Ordering Information

Catalog No.	Finishes	Track Mountings	Luminaires	Lamp
83CY39EWH	Matte White	Intended for ceiling mounting and surface wall mounting 5' or greater from floor. No remote mounting.	Use one of:	39W Ceramic Metal Halide
83CY39EBK	Matte Black		8313 83W4	
83CY39EAL	Metallic Aluminum		8314 83W6 8316	

Features

- Housing:** .10" thick extruded aluminum body with die cast end caps.
- Canopy:** 0.06" aluminum canopy.
- Mounting Arm:** 0.07" extruded aluminum housing.
- Cross Bar:** (not shown) .074" galvanized steel with positive rotation stop. Provides 350° rotation and positive lock every 45°. Mounting to J-Box provides simple hands-free wiring.
- On/Off Switch:** Rocker switch to disconnect power to the ballast.
- Power Receptacle:** 5kv rated, insulated. Accepts power connector from fixture.
- Integral Track Groove:** To mount PowerArc™ Modular spots and wall wash fixtures.

Electrical

Electronic Ballast

Input Voltage:	120 to 277V, 60Hz
Power Factor:	High
Input Power:	44W
Max. Input Current:	0.39A
Total Harmonic Distortion:	<15%
ANSI Code:	M130

Do not use on dimming circuit.

Finish

All painted finishes are baked enamel.

Labels

cUL, UL

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes: