



Ceiling Cutout: 5 1/16" (129 mm) Dia.

Frame-In Kit	Reflector Trim								
<b>C4LVE1RM</b>	Open Downlight	Adjustable Accent	Adjustable Accent	Adjustable 2" Aperture	Adjustable 1 1/4" Pinhole	Lensed Wall Washer	Glasslite Downlight	Glasslyte Adjustable	Lensed Adjustable
	<b>C4MRD</b> 20W-50W MR16 (12V)	<b>C4MRA</b> 20W-50W MR16 (12V)	<b>C4ARA</b> 20W-50W AR70 (12V)	<b>C4MR2</b> 20W-50W MR16 (12V)	<b>C4MRP</b> 20W-50W MR16 (12V)	<b>C4MRL</b> 20W-50W MR16 (12V)	<b>C4MRGD</b> 20W-50W MR16 (12V)	<b>C4MRGA</b> 20W-50W MR16 (12V)	<b>C4MRW</b> 20W-50W MR16 (12V)

**Note:** Magnetic transformers may produce audible sound when used with dimmers, which may be objectionable in acoustically critical areas.

### Features

- Housing:** Hydroformed aluminum, 0.04" (18 ga.). Removable for access to **J-Box and transformer.**
- Mounting Frame:** Die-formed steel, 0.03" (22 ga.) galvanized steel. Accommodates existing ceilings up to 2" thick.
- Locking Clips:** Quick-Lock clips provide ratcheting coarse adjustment for ceiling thickness from 1/2" to 2" thick.
- Fine Adjustment Screws:** Provide pressure to clamp the ceiling material for secure mounting.
- Retaining Springs:** Precision-tooled steel springs secure reflector trim to housing for quick, tool-less installation.
- Quick Electrical Connector:** Keyed to accept plug from reflector trim.
- Junction Box:** 0.03" (22 ga.) galvanized steel. UL listed for 90°C supply connection. Integral cable clamps permit attachment of #14 or #12 ga. non-metallic cable without tools or additional connectors.
- Transformer:** Electronic, 120V 60 Hz, primary, nominal 12V secondary, short circuit and thermal protection, high power factor, THD<10%, dimmable, FCC approved, quiet operation.
- Thermal Protector:** Meets NEC and UL requirements. Insulation must be kept 3" away from fixture sides and wiring compartments and must not be placed above fixture in a manner which will entrap heat.
- Reflector Trim:** Compatible reflector trims are listed above. See separate reflector trim specification sheets for complete catalog numbers, finish, and details.

### Notes:

Vertical aiming for MR16 adjustable trims is 35° max. when used with remodeler. Vertical aiming for AR70 adjustable trims is 25° max. when used with remodeler.

### Electrical/Dimming

Dimming controls: Use with dimmers specially designed for use with electronic transformers, like Lightolier Sunrise™, Multiset™, Momentum QE series. For additional information, see Lightolier Controls Catalog or contact Lightolier Controls at 800-526-2731 or visit website at [www.lolcontrols.com](http://www.lolcontrols.com).

### Labels

CULUS Listed (suitable for damp locations), I.B.E.W.

### Job Information

### Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**