



Ceiling Cutout: 5 3/4" (146 mm) Dia.

Ordering Information

| Reflector Trim | Installation Ring | Socket Harness | Lamp Data |
|---------------------------|-------------------|----------------|----------------------|
| C4MRDVCLEXP Comfort Clear | C4XRM | TKEU75 | MR16 GU5.3, 50W Max. |

Features

- Reflector:** 16 ga. aluminum, 50° visual cutoff to lamp and lamp image.
- Lamp Support:** Die-formed aluminum with spring tension clips to hold lamp and lens allowing fast snap-in, snap-out relamping from below. Matte black finish. Cover glass may be replaced with a color filter or lens accessory.
- Cover Glass:** High temperature, tempered glass. Perimeter frost.
- Gear Harness:** Electronic low voltage transformer with lamp socket and wiring harness. ORDER SEPARATELY. See separate specification sheet for details.
- Trim Retention Springs:** Rust resistant springs secure reflector/housing for quick, toolless installation (quantity of 4).
- Installation Ring:** Cast aluminum ring is painted matte white and has two 17 ga. stainless steel springs that engage in upright position during installation. One touch snap action secures ring in ceiling cutout. ORDER SEPARATELY. See separate Installation Ring specification sheet for more details.

Certifications and Ratings



| Job Information | Type: |
|------------------|-------|
| Job Name: | |
| Cat. No.: | |
| Lamp(s): | |
| Notes: | |

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • A1008