



Ceiling Cutout: 8 1/2" (217 mm) Dia.

Ordering Information

Reflector Trim	Installation Ring	Gear Harness	Lamp Data
C7P38MHCCDPEXP Comfort Clear Diffuse, Polished Flange	C7XRM Matte White	BKMHPU70 BKMHPU15	CDM-R PAR 38 150W Max.

Features

- 1. Reflector Trim:** Clear anodized 16 ga. aluminum with integral flange polished to match inside of cone, 50° visual cutoff to lamp and lamp image.
- 2. Gear Harness:** Electronic metal halide ballast with medium base E27 porcelain socket with nickel plated screw shell (pulse rated) and wiring harness. ORDER SEPARATELY. See separate specification sheet for details.
- 3. Installation Ring:** Cast aluminum ring is painted and has three 17ga. stainless steel springs that engage in upright position during installation. One touch snap action secures ring in ceiling cutout. ORDER SEPARATELY. See separate specification sheet for details.
- 4. Retention Springs:** Rust resistant springs secure trim for quick, tool-less installation (quantity of 4).

Certifications and Ratings



Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes:

631 Airport Road, Fall River, MA 02720 • (508) 679-8131 • Fax (508) 674-4710
 We reserve the right to change details of design, materials and finish.
 www.lightolier.com © 2008 Philips Group • A0608

