



Frame-In Kit



Trimless Reflector



Decorative Tiered Ring

Complete Fixture consists of decorative element, standard Frame-In Kit and Trimless Reflector. Select each separately.

## Ordering Information

Decorative Element Catalog No.	Finish/Color	Trimless Reflector	Frame-In Kit	Dimensions				
				A	B	C	D	E
DT6 PA DT6 PB	Polished Aluminum Polished Brass	For use with all Calculite 6" Compact Fluorescent and Incandescent open trimless downlight reflectors except ProSpec.®	For use with all Calculite 6" Compact Fluorescent and Incandescent open downlight Frame-In Kits except ProSpec.®	7 9/16"	6 9/16"	2 1/8"	1/2"	1 5/8"
DT7 PA DT7 PB	Polished Aluminum Polished Brass	For use with all Calculite 7" Compact Fluorescent and Incandescent open trimless downlight reflectors except ProSpec.®	For use with all Calculite 7" Compact Fluorescent and Incandescent open downlight Frame-In Kits except ProSpec.®	8 15/16"	7 15/16"	2 1/8"	1/2"	1 5/8"

## Features

- Decor Ring:** Two square-section (.05" thick) aluminum rings in tiers. Upper ring 1/4" high. Lower ring 1/2" high.
- Spacer:** Aluminum rod.
- Decorative Knob:** Four placed 90° apart, polished with clear lacquer.
- Trim Ring:** .090" thick aluminum ring with matte white finish.
- Reflector:** See reflector trim for Specification Sheet.
- Frame-In Kit:** See Frame-In Kit for Specification Sheet.
- Mounting Frame Stud:** Four #8-32 screws.

## Lighting Data

For lighting calculations, multiply candlepower values or coefficients of utilization of compact fluorescent fixture without DT6 by 0.9 or DT7 by 0.95.

## Mechanical

Decorative elements securely fastened to four mounting frame studs.

## Finishes/Color

Polished aluminum with clear lacquer.  
Polished aluminum with brass dye lacquer.  
All finishes mentioned above apply to rings, spacers and knobs.

## Labels

U.L. (Damp Location)

## Job Information

## Type:

**Job Name:**

**Cat. No.:**

**Lamp(s):**

**Notes:**