



Ordering Information: Complete fixture consists of Powerhead + Inner Glass + Outer Glass + Suspension Kit. Each sold separately (ie **PS13SA** + **SG03** + **GLS03** + **SK01**).

Spec ID (reference only)	Powerhead	Inner Glass	Outer Glass	Suspension Kit	Lamp	Volts
FA03	PS13SA	SG03	GLS03	*See suspensions below	4-Pin Elect. Twin Tube 13W	120V
FA203	PS132SA	SG03	GLS03		4-Pin Elect. Twin Tube 13W	277V
FA03Q	PS13QSA	SG03	GLS03		4-Pin Quad Tube 13W	120V
FA203Q	PS132QSA	SG03	GLS03		4-Pin Quad Tube 13W	277V
FA0326	PS26SA	SG03	GLS03		4-Pin Quad Tube 26W	120V
FA20326	PS262SA	SG03	GLS03		4-Pin Quad Tube 26W	277V
IA03	PS50SA	SG03	GLS03		T-4 Mini Can. 50W	120V

Suspension Kits:

Cat. No	Finish	Description
SK01	Satin Aluminum	Clear Metallic Straight Cord/Cable, 120" Length, (10') with canopy
SK02	Satin Aluminum	Clear Metallic Straight Cord/Cable, 300" Length, (25') with canopy
ST01	Satin Aluminum	36" Length 3/8" Stem with canopy
ST02	Satin Aluminum	60" Length 3/8" Stem with canopy
CTC	Satin Aluminum	Close to Ceiling Kit with canopy
TM01	Satin Aluminum	Silver Track Mounting Kit with Clear Metallic Straight Cord/Cable, 120" Length, (10') (120V only)

Features

- Power Compartment:** Die Cast and Machined Aluminum Components. Brushed and Clear Lacquer Finish.
- Primary Glass:** Triplex Hand Blown Glass.
- Decorative Glass Assembly:** A conical section of clear hand blown glass with polished edges, die-cast aluminum holder ring and stainless steel support pins.

Lamping (by others)

Incandescent: 50W Max. T-4 Mini Candelabra

Fluorescent: 13W 4-Pin Electronic Twin Tube Specify Lightolier #56964

(**see chart below)

****Compact Fluorescent:**

General Electric	Osram/Sylvania	Philips
(1) 13W Twin Tube 4-Pin Compact Fluorescent Lamp		
N/A	CF13DS/E/*	N/A
(1) 13W Quad Tube 4-Pin Compact Fluorescent Lamp		
F13DBX/SPX*/4P	CF13DD/E/*	PL-C13W/*4P/ALTO
(1) 26W Quad Tube 4-Pin Compact Fluorescent Lamp		
F26BX/*EC04P	CF26DD/E/*	PL-C26W/*4P/ALTO

*Manufacturers Color Temperature Designation

Electrical- Lampholders

Incandescent: E11 Base, Porcelain, Plated Copper Alloy Screw Shell

Compact Fluorescent: 13W Twin: 2GX7 Base, High Impact Thermoset Polymer with Brass Contacts.

13W Quad: G24q-1 Base, High Impact Thermoset Polymer with Brass Contacts.

26W Quad: G24q-3 High impact thermoset polymers with brass contacts.

Ballasts: Fluorescent: Electronic	13 Watts TT		13 Watts QT		26 Watt QT	
Voltage	120	277	120	277	120	277
Max. Watts	16	11	20	14	25	18
Max. Line Current (Amps)	0.136	0.08	0.174	0.114	0.211	0.137

Labels

cULus Listed. Suitable for Damp Locations.

Job Information

Type:

Job Name:

Cat. No.:

Lamp(s):

Notes: